

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: WHITE CAREFREE PLUS SATIN SHN
PRODUCT CODE: 41301

HMIS CODES: H F R P
1 0 0 E

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: REPCOLITE PAINT INC.
ADDRESS: 473 West 17th Street, Holland, MI 49423
EMERGENCY PHONE: 616-396-1275
DATE REVISED : 11-17-92
INFORMATION PHONE: 616-396-1275
NAME OF PREPARER : da

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

| HAZARDOUS COMPONENTS | CAS NUMBER | OCCUPATIONAL EXPOSURE LIMITS | | | VAPOR PRESSURE mm Hg @ TEMP | WEIGHT PERCENT |
|-----------------------------|------------|------------------------------|-----------|-------|--------------------------------|-------------------|
| | | OSHA PEL | ACGIH TLV | OTHER | | |
| Titianium Dioxide | 13463-67-7 | 10 mg/M3 | 10 mg/M3 | | N/A | 20 |
| Anhydrous aluminum silicate | 66402-68-4 | 15 mg/M3 | 10 mg/M3 | | N/A | < 5.0% |
| Hydrous aluminum silicate | 66402-68-4 | 15 mg/M3 | 10 mg/M3 | | N/A | 5 |

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: Not Determined
VAPOR DENSITY: LIGHTER THAN AIR
COATING V.O.C. : 1.32 LB/GL (158 G/L)
SOLUBILITY IN WATER: Dilutable
APPEARANCE AND ODOR: Viscous Liquid, Mild Odor
SPECIFIC GRAVITY (H2O=1): 1.3
EVAPORATION RATE: SLOWER THAN ETHER

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: N/A
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A
EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL
METHOD USED:

ADDITIONAL FIREFIGHTING PROCEDURES

UNUSUAL FIRE AND EXPLOSION HAZARDS

Product will not burn but may spatter if temperature exceeds the boiling point of water. Dried solids can burn.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Restrict area to personnel needed. Major spills should be collected for disposal. Small spills may be flushed to sewer if permitted by federal, state and local regulations.

WASTE DISPOSAL METHOD

Incinerate or bury in a suitable landfill as permitted by government regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Use with adequate ventilation. Avoid contact with skin and clothing. Avoid breathing spray mist.

OTHER PRECAUTIONS

This product contains microcrystalline silica which is a suspected carcinogen and may cause lung disorders if inhaled as dust. When processes that will turn this product into dust, such as spraying and sanding, must be carried out, proper precautions must be taken to avoid inhalation of dusts or mists.

See Section VII-Control Measures

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

Use NIOSH approved dust/mist respirator when spraying or sanding.

VENTILATION

Local exhaust.

PROTECTIVE GLOVES

Vinyl or neoprene.

EYE PROTECTION

Safety glasses.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

WORK/HYGIENIC PRACTICES

===== SECTION IX - DISCLAIMER =====

DISCLAIMER

Conditions of handling, storage, use & disposal of the product covered by this MSDS are beyond the control and knowledge of REPCOLITE PAINTS, INC. Therefore we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product.