



## Safety Data Sheet

### The Armor All/STP Products Company

44 Old Ridgebury Road  
Suite 300  
Danbury, CT 06810  
Tel. 1-203-205-2900

### 1. Product And Company Identification

**Product Name:** ARMOR ALL® Wheel Protectant

**Responsible Party:** The Armor All/STP Products Company  
44 Old Ridgebury Road  
Suite 300  
Danbury, CT 06810

**Information Phone Number:** +1 203-205-2900

**Emergency Phone Number:**

For Medical Emergencies, call 1-866-949-6465 / +1 303-389-1332 (Outside US and Canada)  
For Transportation Emergencies, call 1-800-424-9300 (Chemtrec) +1-703-527-3887 for  
Outside US and Canada (call collect)

**SDS Date Of Preparation:** 06/22/2015

**Product Use and Uses Advised Against:** Automotive maintenance product – For consumer and professional use

### 2. Hazards Identification

Note: This product is a consumer product and is labeled in accordance with the Consumer Product Safety Commission regulations and not OSHA regulations. The requirements for the labeling of consumer products take precedence over OSHA labeling so the actual product label will not contain the OSHA label elements shown below on this SDS.

**GHS Classification:**

Physical:	Health:
Flammable Aerosol Category 1 Gases Under Pressure: Compressed Gas	Toxic to Reproduction Category 2

**GHS Label Elements:**



**Danger!**

Statements of Hazard	Precautionary Phrases
Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Suspected of damaging fertility.	<b>Prevention</b> Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flames, and hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized Container. Do not pierce or burn, even after use.



## Safety Data Sheet

### The Armor All/STP Products Company

44 Old Ridgebury Road  
Suite 300  
Danbury, CT 06810  
Tel. 1-203-205-2900

#### **Prevention Continued**

Wear protective gloves, and eye protection.

#### **Response**

IF exposed or concerned: Get medical attention.

#### **Storage**

Protect from sunlight. Do not exposure to temperatures exceeding 50°C / 122°F.  
Store locked up.

#### **Disposal**

Dispose of contents and container in accordance with local and national regulations

**Hazards not otherwise specified:** None

**Percentage of unknown toxicity:** N/A

### **3. Composition/Information On Ingredients**

Component	CAS No.	Amount
Propellant (propane, isobutene)	74-98-6 / 75-28-5	40-60%
Decamethylcyclopentasiloxane	541-02-6	40-60%
Mixed Cyclosiloxanes	69430-24-6	<3%
Octamethylcyclotetrasiloxane	556-67-2	<1%

**The specific identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.**

### **4. First Aid Measures**

**Inhalation:** If symptoms of exposure develop, remove to fresh air. Seek medical attention if breathing problems or irritation persist.

**Skin Contact:** Rinse skin with plenty of soap and water. If skin irritation develops, seek medical attention.

**Eye Contact:** Flush eyes with plenty of water. If irritation or other symptoms persist, seek medical attention.

**Ingestion:** If the victim is fully conscious, have them drink a glass of water. Get medical assistance by calling a doctor or poison center. Never give anything by mouth to a person who is unconscious or drowsy.

**Most Important Symptoms:** Eye contact may cause mild irritation. Contains components suspected of damaging fertility.

**Indication of Immediate Medical Attention/Special Treatment:** Immediate medical attention should not be required.

### **5. Firefighting Measures**

**Suitable (and Unsuitable) Extinguishing Media:** Use water fog, foam, carbon dioxide or dry chemical. Cool fire exposed containers with water.

**Specific Hazards Arising from the Chemical:** Contents under pressure. Keep away from ignition source and open flames. Exposure of containers to heat and flames can cause them to rupture, often with violent force. Burning may produce carbon monoxide, carbon dioxide, silicone dioxide and formaldehyde.



## Safety Data Sheet

### The Armor All/STP Products Company

44 Old Ridgebury Road  
Suite 300  
Danbury, CT 06810  
Tel. 1-203-205-2900

**Special Fire Fighting Procedures:** Firefighters should always wear positive pressure self-contained breathing apparatus and full protective clothing. Cool fire-exposed containers with water. Use shielding to protect against bursting cans.

### 6: Accidental Release Measures

**Personal Precautions, Protective Equipment, and Emergency Procedures:** Eliminate all sources of ignition. Ventilate area with explosion proof equipment. Wear appropriate protective clothing and equipment.

**Methods and Materials for Containment and Clean-Up:** Place leaking can in a pail in a well-ventilated area away from ignition sources until pressure has dissipated. Collect liquid using inert material and place into a suitable container for disposal.

**Environmental Precautions:** Prevent entry into storm sewers and waterways. Report spill as required by local and national regulations.

### 7. Handling and Storage

**Precautions for Safe Handling:** Avoid contact with eyes. Avoid prolonged contact with skin. Avoid breathing vapors or aerosols. Use with adequate ventilation. Keep away from heat, sparks, hot surfaces and open flames. Wash thoroughly with soap and water after handling. Keep containers closed when not in use. Keep out of the reach of children. Do not puncture or incinerate containers.

**Conditions for Safe Storage, Including any Incompatibilities:** Store in a cool, well-ventilated area, away from incompatible materials. Do not store in direct sunlight or above 120°F. **U.F.C. (NFPA 30B) Level 3 Aerosol.**

### 8. Exposure Controls / Personal Protection

#### Exposure Guidelines:

CHEMICAL	EXPOSURE LIMIT
Propane	1000 ppm TWA OSHA PEL
Isobutane	1000 ppm TWA ACGIH TLV
Decamethylcyclopentasiloxane	None established
Mixed Cyclosiloxanes	None established
Octamethylcyclotetrasiloxane	None established

**Appropriate Engineering Controls:** General ventilation should be adequate for normal use. For operations where the TLV may be exceeded, forced ventilation such as local exhaust may be needed to maintain exposures below applicable limits. Use explosion proof equipment where required.

#### Personal Protective Equipment

**Respiratory Protection:** None under normal use conditions. For operations where the TLV may be exceeded, a NIOSH approved respirator with an organic vapor cartridge and a dust/mist prefilter or supplied air respirator is recommended. Equipment selection depends on contaminant type and concentration. Select in accordance with 29 CFR 1910.134; all applicable laws and regulations; and good industrial hygiene practice.

**Gloves:** Impervious gloves are recommended for prolonged or repeated skin contact.

**Eye Protection:** None required for normal use. Eye protection recommended to avoid eye contact.



## Safety Data Sheet

### The Armor All/STP Products Company

44 Old Ridgebury Road  
Suite 300  
Danbury, CT 06810  
Tel. 1-203-205-2900

**Other Protective Equipment/Clothing:** Appropriate protective clothing as needed to prevent prolonged or repeated skin contact.

## 9. Physical and Chemical Properties

**Appearance And Odor:** Liquid in an aerosol can.

<b>Physical State:</b> Liquid-based aerosol	<b>Odor Threshold:</b> Not determined
<b>pH:</b> Not determined	<b>Vapor Pressure:</b> Not determined
<b>Initial Boiling Point/Range:</b> Not determined	<b>Vapor Density:</b> Not determined
<b>Melting/Freezing Point:</b> Not determined	<b>Percent Volatile:</b> Not determined
<b>Solubility In Water:</b> Slight (Liquid component)	<b>Evaporation Rate:</b> Not determined
<b>Viscosity:</b> Not determined	<b>VOC Content:</b> Not determined
<b>Specific Gravity:</b> ~0.96	<b>Autoignition Temp:</b> Not determined
<b>Coefficient Of Water/Oil Distribution:</b> Not determined	<b>Flammability (solid, gas):</b> Not applicable
<b>Flash Point:</b> 174.2°F (79°C) (Liquid component) Propellant is a flammable gas.	<b>Decomposition Temperature:</b> Not available
<b>Flammability Limits:</b> LEL: 2.1% (Isobutane)	UEL: 9.5%(Propane)

## 10. Stability and Reactivity

**Reactivity:** Not normally reactive.

**Chemical Stability:** Stable under normal storage and handling conditions.

**Conditions to Avoid:** Keep away from excessive heat, sparks and open flames. Containers may rupture at temperatures > 120°F (48.8°C).

**Incompatible Materials:** Strong oxidizing agents.

**Hazardous Decomposition Products:** Thermal decomposition will generate carbon monoxide, carbon dioxide, silicone dioxide and formaldehyde.

## 11. Toxicological Information

### Potential Health Effects:

#### **Acute Hazards:**

**Inhalation:** No adverse effects expected from the normal use of this product.

**Skin Contact:** No adverse effects expected from the normal use of this product.

**Eye Contact:** Contact may cause mild eye irritation.

**Ingestion:** Ingestion is an unlikely route exposure for aerosol products. Swallowing may cause gastrointestinal disturbances.

**Chronic Effects:** Contains components suspected of damaging fertility.

**Carcinogenicity Listing:** None of the components is listed as a carcinogen or potential carcinogen by IARC, NTP, ACGIH or OSHA.



## Safety Data Sheet

### The Armor All/STP Products Company

44 Old Ridgebury Road  
Suite 300  
Danbury, CT 06810  
Tel. 1-203-205-2900

### **Numerical Measures of Toxicity:**

Propane:	LC50 Rat Inhalation >800,000 ppm
Isobutane:	LC50 Rat Inhalation 658 mg/l/4 hr.
Decamethylcyclopentasiloxane	LC50 Rat Inhalation >2,700 mg/m <sup>3</sup> /4 hr. LD50 Rat Oral >24,134 mg/kg LD50 Rabbit Dermal 16 mL/kg
Mixed Cyclosiloxanes:	LD50 Rat Oral >16 mL/kg LD50 Rabbit Dermal >16 mL/kg
Octamethylcyclotetrasiloxane:	LC50 Rat Inhalation 3,600 mg/m <sup>3</sup> /4 hr. LD50 Rat Oral 1,540 mg/kg LD50 Rabbit Dermal 762 mg/kg

## 12. Ecological Information

**Ecotoxicity:** No ecotoxicity data is currently available for product.

**Persistence and Degradability:** No data available for product.

**Bio accumulative Potential:** No data available for product.

**Mobility in Soil:** No data available for product.

**Other Adverse Effects:** No data available

## 13. Disposal Considerations

Dispose of in accordance with all local, state/provincial and federal regulations. Offer empty containers for recycling.

## 14. Transport Information

**DOT Hazardous Materials Description:** UN1950, Aerosols, Class 2.1, Ltd Qty

**IMDG Dangerous Goods Description:** UN1950, Aerosols, 2.1, Ltd Qty

**IATA International Air Transport Association:** UN1950, Aerosols, Class 2.1, Ltd Qty

## 15. Regulatory Information

### **United States:**

**EPA TSCA INVENTORY:** All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

**CERCLA Section 103:** This product has no RQ. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.



## Safety Data Sheet

### The Armor All/STP Products Company

44 Old Ridgebury Road  
Suite 300  
Danbury, CT 06810  
Tel. 1-203-205-2900

**SARA Hazard Category (311/312):** Fire Hazard, Sudden Release of Pressure, Chronic Health.

**SARA 313:** This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372): None

### Canada:

**Canadian Environmental Protection Act:** All of the ingredients are listed on the Canadian DSL.

This SDS has been prepared according to the criteria of the Controlled Products Regulation (CPR) and the SDS contains all of the information required by the CPR.

### 16. Other Information

NFPA Rating (NFPA 704):	Health: 0	Fire: 4	Instability: 0
HMIS Rating:	Health: 1*	Fire: 2	Physical Hazard: 0

DATE OF CURRENT REVISION: 06/22/2015

REVISION SUMMARY: Update to OSHA HazCom 2012 GHS format. Changes to all sections.

DATE OF PREVIOUS REVISION: 03/21/2012

DATA SUPPLIED IS FOR USE ONLY IN CONNECTION WITH OCCUPATIONAL SAFETY AND HEALTH