

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 870

Product name Netcare Vandalism Mark Remover

Effective date 21-Oct-2010

Company information Network Services Company

1100 East Woodfield Rd, Suite 200 Schaumburg, IL 60173 United States

Company phone General Assistance 630-543-7600

Emergency telephone US 800-424-9300 Emergency telephone outside US 703-527-3887

Version # 04

Supersedes date 06-Jun-2008

2. Hazards Identification

Emergency overview EXTREMELY FLAMMABLE LIQUID AND VAPOR. FLAMMABLE

CONTENTS UNDER PRESSURE. Aerosol. Will be easily ignited by heat, spark or flames. Harmful in contact with eyes. Cancer hazard. Irritating to skin. Irritating to

respiratory system. Prolonged exposure may cause chronic effects.

Potential health effects

Routes of exposure Ingestion. Inhalation. Skin contact.

Eyes Contact may irritate or burn eyes. Eye contact may result in corneal injury.

Skin Irritating to skin. Prolonged or repeated contact can result in defatting and drying of the

skin which may result in skin irritation and dermatitis (rash).

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

Irritating to respiratory system. Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. Harmful if swallowed. May cause delayed

lung damage.

Target organs Kidney. Central nervous system. Liver. Lungs. Respiratory system.

Chronic effects Conjunctiva. Liver injury may occur. Kidney injury may occur. May cause central nervous

system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. May cause delayed lung damage. Prolonged skin contact may defat the skin and produce dermatitis.

Signs and symptoms Discomfort in the chest. Corneal damage. Narcosis. Liver enlargement. Jaundice.

Conjunctivitis. Defatting of the skin. Irritation.

3. Composition / Information on Ingredients

Components	CAS#	Percent
Methylene Chloride	75-09-2	40 - 50
n-Butane	106-97-8	20 - 30
Toluene	108-88-3	10 - 15
Perchloroethylene	127-18-4	8 - 10
Propane	74-98-6	8 - 10
Propylene Oxide	75-56-9	0.1 - 0.5
Non-hazardous and other components below reportable levels		1 - 2.5

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact

lenses, if present and easy to do. Get medical attention immediately.

Product name: Netcare Vandalism Mark Remover

Product #: 870-001 Revision date: 21-OCT-2010 Print date: 21-OCT-2010

Skin contact Remove and isolate contaminated clothing and shoes. Wash off with warm water and

soap. Get medical attention if irritation develops or persists. For minor skin contact, avoid

spreading material on unaffected skin.

Inhalation

Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician if symptoms develop or persist.

Ingestion

Never give anything by mouth to a victim who is unconscious or is having convulsions. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

5. Fire Fighting Measures

Flammable properties **Extinguishing media**

the chemical

Vapor or gas may spread to distant ignition sources and flash back.

Suitable extinguishing media

Foam. Dry chemical. Carbon dioxide (CO2).

Protection of firefighters

Specific hazards arising from

Fire may produce irritating, corrosive and/or toxic gases.

Protective equipment and precautions for firefighters

In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

6. Accidental Release Measures

Methods for containment

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable.

Methods for cleaning up

Should not be released into the environment.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not smoke while using or until sprayed surface is thoroughly dry. Do not use if spray button is missing or defective. Use only with adequate ventilation. Do not get this material in contact with eyes. Do not get this material in contact with skin. Wear personal protective equipment. Avoid prolonged exposure.

Storage

Level 1 Aerosol.

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Avoid exposure to long periods of sunlight. Keep in an area equipped with sprinklers. Keep out of the reach of children.

8. Exposure Controls / Personal Protection

Exposure limits

ACGIH

Components	CAS#	TWA	STEL	Ceiling
Methylene Chloride	75-09-2	50 ppm	Not established	Not established
n-Butane	106-97-8	1000 ppm	Not established	Not established
Toluene	108-88-3	20 ppm	Not established	Not established
Perchloroethylene	127-18-4	25 ppm	100 ppm	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
Propylene Oxide	75-56-9	2 ppm	Not established	Not established

MSDS US Product #: 870-001 Revision date: 21-OCT-2010 Print date: 21-OCT-2010

OSHA

Components	CAS#	TWA	STEL	Ceiling
Methylene Chloride	75-09-2	25 ppm	125 ppm	Not established
Toluene	108-88-3	200 ppm	Not established	300 ppm
Perchloroethylene	127-18-4	100 ppm	Not established	200 ppm
Propane	74-98-6	1000 ppm	Not established	Not established
Propylene Oxide	75-56-9	100 ppm	Not established	Not established

Personal protective equipment

Eye / face protection Wear chemical goggles.

Skin protection Wear appropriate chemical resistant clothing. Protective gloves. **Respiratory protection** Wear positive pressure self-contained breathing apparatus (SCBA).

9. Physical & Chemical Properties

Appearance Compressed liquefied gas. **Boiling point** 102.2 °F (38.9 °C) estimated

Color Pale yellow

Density 0.8933 g/cm3 estimated **Flammability (HOC)** 18.61 kJ/g estimated

Flash back Yes

Flash point -156 °F (-104.4 °C) Propellant

Form Aerosol.

Freezing point Not available
Odor Solvent.

pH Not applicable

Physical state Liquid.

Pressure 40 - 55 psig @ 70F

SolubilityNegligibleSpecific gravity0.8934 estimated

10. Chemical Stability & Reactivity Information

Chemical stability Risk of ignition. Stable at normal conditions.

Conditions to avoid Heat, flames and sparks.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products Hydrogen chloride. Irritants. Toxic gas. May include oxides of oxides of carbon.

11. Toxicological Information

Acute effects Acute LC50: 82 mg/l/4h estimated, Rat, Inhalation

Acute LD50: 55930 mg/kg estimated, Rat, Dermal

Component analysis - LD50

Toxicology Data - Selected LD50s and LC50s

Methylene Chloride 75-09-2 Oral LD50 Rat >2000 mg/kg; Inhalation LC50 Rat 76000 mg/m3 4 h

n-Butane 106-97-8 Inhalation LC50 Rat 658 mg/L 4 h

Perchloroethylene 127-18-4 Inhalation LC50 Rat 4000 ppm 4 h; Oral LD50 Rat 2629 mg/kg; Dermal LD50 Mouse

2800 mg/kg

Propane 74-98-6 Inhalation LC50 Rat 658 mg/L 4 h

Propylene Oxide 75-56-9 Oral LD50 Rat 520 mg/kg

Toluene 108-88-3 Inhalation LC50 Rat 12.5 mg/L 4 h; Inhalation LC50 Rat >26700 ppm 1 h; Oral LD50

Rat 636 mg/kg; Dermal LD50 Rabbit 8390 mg/kg; Dermal LD50 Rat 12124 mg/kg

Sensitization Not expected to be hazardous by OSHA criteria.

Carcinogenicity Hazardous by OSHA criteria.

IARC - Group 2A (Probably Carcinogenic to Humans)

Perchloroethylene 127-18-4 Monograph 63 [1995]; Supplement 7 [1987]

IARC - Group 2B (Possibly Carcinogenic to Humans)

Methylene Chloride75-09-2Monograph 71 [1999]; Supplement 7 [1987]Propylene Oxide75-56-9Monograph 60 [1994]; Supplement 7 [1987]

Product name: Netcare Vandalism Mark Remover MSDS US

12. Ecological Information

Ecotoxicity LC50 32.2 mg/L, Fish, 96.00 Hours,

EC50 30.14 mg/L, Daphnia, 48.00 Hours, IC50 633 mg/L, Algae, 72.00 Hours,

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 F

D039: Waste Tetrachloroethylene

Disposal instructions Contents under pressure. Dispose of this material and its container at hazardous or

special waste collection point. Do not allow this material to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose

in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name Consumer commodity

Hazard class ORM-D Subsidiary hazard class None

Additional information:

Packaging exceptions 156, 306 156, 306 Packaging non bulk None Packaging bulk

IMDG

Basic shipping requirements:

AEROSOLS Proper shipping name

2.1 **Hazard class** Subsidiary hazard class 6.1 **UN** number 1950

Marine pollutant Tetrachloroethylene

Additional information:

NOT a LTQ QTY Packaging exceptions

2.1, 6.1 Labels required

IATA

Basic shipping requirements:

Proper shipping name Aerosols, flammable, containing substances in Division

6.1, Packing Group III

Hazard class 2.1 Subsidiary hazard class 6.1 **UN** number 1950

Additional information:

LTD QTY **Packaging exceptions** Labels required 2.1, 6.1



15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

Methylene Chloride 75-09-2 0.1 % de minimis concentration Perchloroethylene 127-18-4 0.1 % de minimis concentration Propylene Oxide 75-56-9 0.1 % de minimis concentration Toluene 108-88-3 1.0 % de minimis concentration

Product #: 870-001 Revision date: 21-OCT-2010 Print date: 21-OCT-2010

Product name: Netcare Vandalism Mark Remover



Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous Yes

chemical

CERCLA (Superfund) reportable quantity

Methylene Chloride: 1000.0000

Toluene: 1000.0000 Perchloroethylene: 100.0000 Propylene Oxide: 100.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 302 extremely No

hazardous substance

Section 311 hazardous chemical Yes

Hazard categories (311/312) Immediate Hazard - Yes

> Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

Inventory status

State regulations

On inventory (yes/no)* Country(s) or region Inventory name Inventory of Existing Chemical Substances in China (IECSC) China European Inventory of New and Existing Chemicals (EINECS) Europe Nο Europe European List of Notified Chemical Substances (ELINCS) No Japan Inventory of Existing and New Chemical Substances (ENCS) No Korea Existing Chemicals List (ECL) No United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

WARNING: This product contains a chemical known to the State of California to cause

cancer and birth defects or other reproductive harm.

U.S. - Pennsylvania - RTK (Right to Know) List

Methylene Chloride 75-09-2 Environmental hazard; Special hazardous substance

n-Butane 106-97-8 Present

Perchloroethylene 127-18-4 Environmental hazard; Special hazardous substance

Propane 74-98-6 Present

Propylene Oxide 75-56-9 Environmental hazard; Special hazardous substance

108-88-3 Environmental hazard Toluene

16. Other Information

HMIS Trademark Statement Further information

HMIS® ratings Health: 2*

Flammability: 2 Physical hazard: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our

> knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification, The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified

in the text.

MSDS sections updated Product and Company Identification: Product Review

Physical & Chemical Properties: Physical & Chemical Properties

Physical & Chemical Properties: Appearance

Transport Information: Product Shipping Name/Packing Group

Prepared by Regulatory Compliance

Product name: Netcare Vandalism Mark Remover MSDS US