PRODUCT NAME: CIELING WHITE SATIN LATEX FLAT HMIS CODES: H F R P

MANUFACTURER'S NAME: REPCOLITE PAINT INC.

ADDRESS: 473 West 17th Street, Holland, MI 49423

EMERGENCY PHONE: 616-396-1275 INFORMATION PHONE: 616-396-1275

DATE REVISED : 07-31-92 NAME OF PREPARER : da

REASON REVISED : NEW FORMULA

======= SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION ========

| | | OCCUPATIONAL EXPOSURE LIMITS | | VAPOR PRESSURE | WEIGHT |
|-----------------------------|------------|------------------------------|-----------------|----------------|---------|
| HAZARDOUS COMPONENTS | CAS NUMBER | OSHA PEL | ACGIH TLV OTHER | mm Hg & TEMP | PERCENT |
| Titianium Dioxide | 13463-67-7 | 10 mg/H3 | 10 mg/H3 | N/A | 15 |
| Anhydrous aluminum silicate | 66402-68-4 | | 10 mg/H3 | N/A | 20 |
| Calcium Carbonate | 1317-65-3 | | 10 mg/M3 | N/A | 10 |

*** No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. ***

BOILING POINT: Not Determined SPECIFIC GRAVITY (H20=1): 1.4

VAPOR DENSITY: LIGHTER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER

COATING V.O.C.: 0.84 LB/GL (101 G/L)

SOLUBILITY IN WATER: Dilutable

APPEARANCE AND ODOR: Viscous Liquid, Mild Odor

FLASH POINT: N/A METHOD USED:

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: N/A UPPER: N/A

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL

SPECIAL FIREFIGHTING PROCEDURES

JUAL FIRE AND EXPLOSION HAZARDS

c will not burn but may spatter if temperature exceeds the boiling point of water. Dried solids can burn.

STABILITY: STABLE Cr TITIONS TO AVOID

INCOMPATIBILITY (MATERIALS TO AVOID)

HAZARDOUS DECOMPOSITION OR BYPRODUCTS
Burning of dried solids may give off oxides of carbon and nitrogen.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
May contain products the will irritate mucous membrane and respiratory tract. Inhalation may produce symptoms of headache and nausea in poorly ventilated areas.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE Prolonged contact may produce temporary reddening of skin. Direct contact may cause eye irratation.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

I ISTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE
No evedence of adverse effects.

HEALTH HAZARDS (ACUTE AND CHRONIC)
Hone known.

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE Kone known.

EMERGENCY AND FIRST AID PROCEDURES Ingestion: No harmful effects expected. Inhalation: No emergency care anticipated. Skin: Wash effected areas with soap and water. Eyes: Immediatly flus eyes with water.

| SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE ========= |
|---|
| STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED ct area to personel needed. Major spills should be collected for disposal. Small spills may be flushed to sever if ced by federal, state and local regulations. |
| AnoTE DISPOSAL METHOD incinerate or bury in a suitable landfill as permitted by government regulations. |
| PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING see with adequate ventilation. Avoid contact with skin and clothing. Avoid breathing spray mist. |
| OTHER PRECAUTIONS |
| SECTION VIII - CONTROL MEASURES |
| RESPIRATORY PROTECTION se a NIOSH approved dust/mist reaspirator when spraying. |
| ·ILATION exhaust. |
| PROTECTIVE GLOVES /inyl or neoprene. |
| EYE PROTECTION afety glasses. |
| OTHER PROTECTIVE CLOTHING OR EQUIPMENT |
| JORK/HYGIENIC PRACTICES |
| |
| DISCLAIMER The conditions of handling, storage, use & disposal of the product covered by this MSDS are beyond the control and know- edge of REPCOLITE PAINTS, INC. Therefore we do not assume responsibility and expressly disclaim liability for loss, samage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product. |
| |